

Jednolúčový pluh BOMET Libra (šírka tela pluhu: 30 - 50)

	Počet pluhov	Pracovná šírka	Vzdialenosť medzi pluhmi	Výška pod rámom	Hmotnosť	Požadovaný výkon				Cena bez DPH
-	ks	m	cm	cm	kg	kW	HP	-	-	EUR
PROTECTION BY SCREWS										
U068	3	0,9 - 1,5	90	83	830	55-66	75-90	✓	-	5227
U068	3	0,9 - 1,5	90	83	830	55-66	75-90	-	✓	5428
U068/1	3+1	1,2 - 2,0	90	83	1000	74-88	100-120	✓	-	6383
U068/1	3+1	1,2 - 2,0	90	83	1000	74-88	100-120	-	✓	6749
U068/2	4	1,2 - 2,0	90	83	1000	74-88	100-120	✓	-	6383
U068/2	4	1,2 - 2,0	90	83	1000	74-88	100-120	-	✓	6749
U068/3	4+1 / 5	1,5 - 2,5	90	83	1180	92-110	125-150	✓	-	7540
U068/3	4+1 / 5	1,5 - 2,5	90	83	1180	92-110	125-150	-	✓	8071
Ochrana pružinami										
U068	3	0,9 - 1,5	90	83	920	55-66	75-90	✓	-	6383
U068	3	0,9 - 1,5	90	83	920	55-66	75-90	-	✓	6631
U068/1	3+1	1,2 - 2,0	90	83	1120	74-88	100-120	✓	-	7823
U068/1	3+1	1,2 - 2,0	90	83	1120	74-88	100-120	-	✓	8177
U068/2	4	1,2 - 2,0	90	83	1120	74-88	100-120	✓	-	7823
U068/2	4	1,2 - 2,0	90	83	1120	74-88	100-120	-	✓	8177
U068/3	4+1 / 5	1,5 - 2,5	90	83	1330	92-110	125-150	✓	-	9251
U068/3	4+1 / 5	1,5 - 2,5	90	83	1330	92-110	125-150	-	✓	9723