

Jednolúčový pluh BOMET Libra (šírka tela pluhu: 25 - 30 - 35)

	Počet pluhov	Pracovná šírka	Vzdialenosť medzi pluhmi	Výška pod rámom	Hmotnosť	Požadovaný výkon				Cena bez DPH
-	ks	m	cm	cm	kg	kW	HP	-	-	EUR
PROTECTION BY SCREWS										
U030	2	0,5 / 0,6 / 0,7	80	72	470	22-35	30-48	✓	-	3032
U030	2	0,5 / 0,6 / 0,7	80	72	470	22-35	30-48	-	✓	3197
U030/1	2+1	0,75 / 0,9 / 1,05	80	72	640	30-50	40-68	✓	-	3658
U030/1	2+1	0,75 / 0,9 / 1,05	80	72	640	30-50	40-68	-	✓	3905
U030/2	3	0,75 / 0,9 / 1,05	80	72	640	30-50	40-68	✓	-	3658
U030/2	3	0,75 / 0,9 / 1,05	80	72	640	30-50	40-68	-	✓	3905
U030/3	3+1 / 4	1,0 / 1,2 / 1,4	80	72	780	40-57	55-78	✓	-	4295
U030/3	3+1 / 4	1,0 / 1,2 / 1,4	80	72	780	40-57	55-78	-	✓	4625