



Obojstranný pluh BOMET Leo (šířka tela pluhu: 34 - 42 - 50)

-	Počet pluhov	Pracovní šířka	Vzdialenosť medzi pluhmi	Výška pod rámom	Hmotnosť	Požadovaný výkon				Cena bez DPH
	ks	m	cm	cm	kg	kW	HP			EUR
Type your text OCHRANA SKRUTKAMI										
U052	3	1,02 / 1,26 / 1,5	100	82	1320	55-66	75-90	✓	-	10738
U052	3	1,02 / 1,26 / 1,5	100	82	1320	55-66	75-90	-	✓	13113
U052/1	3+1	1,36 / 1,68 / 2,0	100	82	1595	74-88	100-120	✓	-	13098
U052/1	3+1	1,36 / 1,68 / 2,0	100	82	1595	74-88	100-120	-	✓	14278
U052/2	4	1,36 / 1,68 / 2,0	100	82	1595	74-88	100-120	✓	-	13098
U052/2	4	1,36 / 1,68 / 2,0	100	82	1595	74-88	100-120	-	✓	14278
U052/3	4+1 / 5	1,6 / 2,1 / 2,5	100	82	1835	92-110	125-150	✓	-	15458
U052/3	4+1 / 5	1,6 / 2,1 / 2,5	100	82	1835	92-110	125-150	-	✓	18254
OCHRANA PRUŽINAMI										
U052	3	1,02 / 1,26 / 1,5	100	82	1350	55-66	75-90	✓	-	11587
U052	3	1,02 / 1,26 / 1,5	100	82	1350	55-66	75-90	-	✓	12248
U052/1	3+1	1,36 / 1,68 / 2,0	100	82	1635	74-88	100-120	✓	-	14514
U052/1	3+1	1,36 / 1,68 / 2,0	100	82	1635	74-88	100-120	-	✓	15458
U052/2	4	1,36 / 1,68 / 2,0	100	82	1635	74-88	100-120	✓	-	14514
U052/2	4	1,36 / 1,68 / 2,0	100	82	1635	74-88	100-120	-	✓	15458
U052/3	4+1 / 5	1,6 / 2,1 / 2,5	100	82	1885	92-110	125-150	✓	-	17464
U052/3	4+1 / 5	1,6 / 2,1 / 2,5	100	82	1885	92-110	125-150	-	✓	18644
OCHRANA HYDRAULICKÝM VALCOM										
U052	3	1,02 / 1,26 / 1,5	100	82	1335	55-66	75-90	✓	-	12637
U052	3	1,02 / 1,26 / 1,5	100	82	1335	55-66	75-90	-	✓	13298
U052/1	3+1	1,36 / 1,68 / 2,0	100	82	1615	74-88	100-120	✓	-	15257
U052/1	3+1	1,36 / 1,68 / 2,0	100	82	1615	74-88	100-120	-	✓	16189
U052/2	4	1,36 / 1,68 / 2,0	100	82	1615	74-88	100-120	✓	-	15257
U052/2	4	1,36 / 1,68 / 2,0	100	82	1615	74-88	100-120	-	✓	16189
U052/3	4+1 / 5	1,6 / 2,1 / 2,5	100	82	1855	92-110	125-150	✓	-	17865
U052/3	4+1 / 5	1,6 / 2,1 / 2,5	100	82	1855	92-110	125-150	-	✓	19080